

High Performance LiDAR Sensors for KINEMATIC Laser Scanning

VUX-1HA (High Accuracy) **Typical Applications**

- indoor and outdoor laser mapping
- tunnel profile measurements
- railway applications like clearance analysis, etc.

VUX-1UAV Typical Applications

- topography in open-cast mining
- agriculture and forestry
- terrain and canvon mapping
- corridor mapping

VUX-1LR (Long Range) Typical Applications

- corridor mapping: power line, railway track and pipeline inspection • surveying of urban environments
- archeology and cultural heritage documentation



www.riegl.com

RIEGL USA Inc.

RIEGL Japan Ltd.

RIEGL China Ltd.

RIEGL VUX®-1 Series



- compact, rugged and very lightweight High Accuracy LiDAR sensor
- easily mountable to whatsoever type of moving platform
- Laser Pulse Repetition Rate PRR > 1 MHz, high accuracy 5 mm

Eye Safety Class	Laser Class 1
Max. Range @ Target Reflectivity 80%	420 m
Max. Range @ Target Reflectivity 10%	150 m
Minimum Range	1.2 m
Accuracy/Precision	5 mm / 3 mm
Max. Effective Measurement Rate	1,000,000 meas./sec
Max. Scan Speed	250 scans/sec
Field of View (FOV)	360°

RIEGL VUX®-1UAV

- compact, rugged and very lightweight LiDAR sensor for UAV integration
- easily mountable to professional UAS/UAV/RPAS, etc.
- fully integrated system solution *RIEGL* VUX-SYS and RiCOPTER available

Eye Safety Class	Laser Class 1
Max. Range @ Target Reflectivity 60%	920 m
Max. Range @ Target Reflectivity 20%	550 m
Minimum Range	3 m
Accuracy/Precision	10 mm / 5 mm
Max. Effective Measurement Rate	500,000 meas./sec
Max. Scan Speed	200 scans/sec
Field of View (FOV)	330°
Max. Operating Flight Altitude AGL	350 m / 1,150 ft

RIEGL VUX®-1LR




- compact, rugged and very lightweight Long Range LiDAR sensor
- ideally suited for airborne surveying from helicopters
- fully integrated system solution *RIEGL* VP-1 Helicopter Pod available for user-friendly mounting to helicopters

Eye Safety Class	Laser Class 1
Max. Range @ Target Reflectivity 60%	1,350 m
Max. Range @ Target Reflectivity 20%	820 m
Minimum Range	5 m
Accuracy/Precision	15 mm / 10 mm
Max. Effective Measurement Rate	750,000 meas./sec
Max. Scan Speed	200 scans/sec
Field of View (FOV)	330°
Max. Operating Flight Altitude AGL	530 m / 1,740 ft



RIEGL VUX®-1HA scan data, transportation infrastructure mapping at highway speed



RIEGL VUX®-1UAV scan data, powerline inspection



RIEGL VUX®-1LR scan data, urban area



Further Information

RIEGL VUX-1UAV

Data She









youtube.com/rieglims

Copyright *RIEGL* Laser Measurement Systems GmbH © 2017– All rights reserved. Use of this data sheet other than for personal purposes requires *RIEGLs* written consent.

This data sheet is compiled with care. However, errors cannot be fully excluded and alternations might be necessary.

www.riegl.com

